



429.00 EUR

incl. 19% VAT, plus [shipping](#)

- JC390F841XX34B
- JC390F841VXX34B



January 2023: Intel i225V LAN instead of i211AT

- Intel® Apollo Lake SoC Processor
- 1 * SO-DIMM DDR3L 1866MHz up to 8GB
- 4 * USB3.0, 2 * COM, 2 * HDMI, 1 * Audio, 2 * RJ45
- Product Dimension: 185 x 165 x 48 mm
- DC-12V_5A_60W Lockable Adapter

MB Model	- JNF841-J3455					
Part No	No Expansion	8 LAN	8 COM	4 COM+4 LAN	16-bits GPIO	4 COM+16-bits GPIO
	-	-	-	-	-	-
	HBJC390F841XX34B	HBJC390F841AA34B	HBJC390F841CC34B	HBJC390F841CA34B	HBJC390F841XG34B	HBJC390F841CG34B
	-	-	-	-	-	-
	HBJC390F841WXX34B (Wifi)	HBJC390F841WAA34B (Wifi)	HBJC390F841WCC34B (Wifi)	HBJC390F841WCA34B (Wifi)	HBJC390F841WXC34B (Wifi)	HBJC390F841WCG34B (Wifi)
	4 LAN+16-bits GPIO	32-bits GPIO	4 USB 3.0	4 COM+4 USB 3.0	4 LAN+4 USB 3.0	16-bits GPIO+4 USB 3.0
-	-	-	-	-	-	
HBJC390F841AG34B	HBJC390F841GG34B	HBJC390F841XU34B	HBJC390F841CU34B	HBJC390F841AU34B	HBJC390F841GU34B	
-	-	-	-	-	-	
HBJC390F841WAG34B (Wifi)	HBJC390F841WGG34B (Wifi)	HBJC390F841WXU34B (Wifi)	HBJC390F841WCU34B (Wifi)	HBJC390F841WAU34B (Wifi)	HBJC390F841WGU34B (Wifi)	
BIOS	- AMI EFI Flash ROM					
CPU/Chipset	- Intel® Apollo Lake SoC Processor (J3455)					
Memory	1 * SO-DIMM DDR3L-1866 up to 8GB					
Storage	- 1 * 2.5" SATA drive bay (only support 2.5" HDD with a height ≤ 10mm) - 1 * M.2 (M-key SATA Interface 2280)					
Network	- 2 * Intel i225V Gigabit LAN - 2 * Full size Mini-PCIe slot (Can be installed WiFi module & 3G/4G module) - 1 * SIM slot					
TPM	- TPM2.0 on-board (option)					

Rear Panel I/O	<ul style="list-style-type: none"> - 4 * USB3.0 - 2 * HDMI 1.4 - 2 * RJ45 - 1 * Audio combo Jack (Line-out & MIC-in) - 2 * COM (RS232) - 2 * Antenna holes (WiFi Only) - Lockable DC-In jack
Front Panel I/O	<ul style="list-style-type: none"> - 1 * Power button + LED - 1 * HDD LED - COM (Expansion Module, support RS232/422/485) - Intel Gigabit LAN (Expansion Module) - USB3.0 (Expansion Module) - 16-Bits GPIO (Expansion Module)
Power Source	<ul style="list-style-type: none"> - 60W AC-DC Adapter / DC12V-5A - AC 90~240V input
Compliance	<ul style="list-style-type: none"> - CE, FCC, LVD
Temperature	<ul style="list-style-type: none"> - Operating temperature: 0 ~ 50° C (Under the condition of using 2.5" HDD) - Storage Temperature: -20 ~ 60° C (Under the condition of using mSATA) <p>(The test environment is closed and windless)</p> <ul style="list-style-type: none"> - Storage Temperature: -10 ~ 70° C - Humidity : 90% , non-condensing
Dimensions	<ul style="list-style-type: none"> - 185 (W) x 165 (D) x 48 (H) mm
Packing	<ul style="list-style-type: none"> - Net Weight: 2.4KG - Gross Weight: 3.4KG - Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm
OS Support	<ul style="list-style-type: none"> - Windows 10, Linux